



- Economical solar inverter with affordable price
- Easy install, one battery 12vdc
- Wide PV input voltage range starts from 30VDC
- Battery independent design
- Built-in 80A MPPT solar charger
- Battery equalization function to optimize battery performance and extend lifecycle
- Built-in anti-dust kit



Axpert VM II Off-Grid Inverter Specification

MODEL	Axpert VM II 1.5K
Rated Power	1500VA/1500W
INPUT	
Voltage	230 VAC
Selectable Voltage Range	170-280 VAC (For Personal Computers); 90-280 VAC (For Home Appliances)
Frequency Range	50 Hz/60 Hz (Auto sensing)
OUTPUT	
AC Voltage Regulation (Batt. Mode)	230VAC ± 5%
Output Power	1500W with PV & battery; 1200W with battery only
Surge Power	2400VA
Efficiency (Peak)	93%
Transfer Time	10 ms (For Personal Computers) ; 20 ms (For Home Appliances)
Waveform	Pure sine wave
BATTERY	
Battery Voltage	12 VDC
Floating Charge Voltage	13.5 VDC
Overcharge Protection	16 VDC
SOLAR CHARGER & AC CHARGER	
Solar Charger Type	MPPT
Maximum PV Array Open Circuit Voltage	350 VDC
Maximum PV Array Power	2000W
MPP Range @ Operating Voltage	30-300 VDC(30V-60V with battery)
Maximum Solar Charge Current	80 A
Maximum AC Charge Current	80 A
Maximum Charge Current	80 A
PHYSICAL	
Dimension, D x W x H (mm)	90 x 288 x 357
Net Weight (kgs)	6.5
Communication Interface	RS232
ENVIRONMENT	
Humidity	5% to 95% Relative Humidity (Non-condensing)
Operating Temperature	-10°C to 50°C
Storage Temperature	-15°C to 60°C

Product specifications are subject to change without further notice.